

# 2000nm 1x3/3x3

1x3/3x3

FBT Coupler

400-2050nm



/

		1x3	3x3
-		1x3	3x3
nm		2000	
nm		± 20	
%		1x3 33/33/33(only 3x3)	
dB		0.8	1.0
%		± 5(1x3) / ± 10(3x3)	
W		0.5 2 5	
-		SMF fiber	
-		FC/APC	
m		1	
mm		3.0x54 or 4.0x60( )	
		-40 +85	
		-50 +85	

25

5dB

	Through Port	Coupling Port
40/20/40	± 5.0	± 6.0
35/30/35	± 4.0	± 5.0
33/33/33	± 6.0	± 6.0
30/40/30	± 4.0	± 3.0
25/50/25	± 3.5	± 2.4
20/60/20	± 3.3	± 2.0
15/70/15	± 3.0	± 1.8
10/80/10	± 2.8	± 1.6
5/90/5	± 2.5	± 1.5



13- 1x3 33- 3x3	2000- 2000nm	424- 40/20/40 333- 33/33/33 343- 30/40/30 252- 25/50/25 262- 20/60/20 171- 15/70/15 181- 10/80/10 595- 5/90/5	L- 0. 5W 1- 1W 5- 5W S-	S2- SMF- 28e S19- SM950	08- 0. 8m 10- 1. 0m 15- 1. 5m S-	B- 250um L- 900um S-	N- None FP- FC/PC FA- FC/APC S-	

MCFBT- 13- 2000- 333- L- S19- 10- L- FA

, 1x3 , 2000nm, 33: 33: 33, 500 , 4. 0x60mm  
SM950, 1 , 900um , FC/APC